



## Hydrolux HL 5

### Mini leak detector

#### Benefits:

- ▶ **Excellent, optimized audio characteristics**
- ▶ **3 optimized filter settings**
- ▶ **Mute setting (no static noise in the headphones)**
- ▶ **Wireless noise transmission**
- ▶ **Built-in LED light for night work**



#### Description

The new Hydrolux HL 5 from SebaKMT is a professional and very flexible mini water leak detection unit with both visual and audible indication of the leak and with wireless transmission of the leak noise. It belongs in the jacket pocket of every water specialist and plumber for an instant, on the spot leak monitoring check.

Wireless transmission of the leak noise to the headphones provides maximum freedom of movement. The extremely sensitive piezo-ceramic sensors with automatic level control enable excellent quality analyses even on plastic pipes.

Whether used as a sensor rod or as a ground microphone: three filter settings allow the unit to be ideally configured for every leak situation.

The built-in light is great for dark corners and is a very practical companion for night work and for cellars.

#### The benefits at a glance

- ▶ Pocketsize
- ▶ Mute setting (no static noise in the headphones)
- ▶ 3 optimized filter settings
- ▶ Excellent, optimised audio characteristics
- ▶ Optional adapter, for use as a ground microphone
- ▶ Easy, one-button operation
- ▶ Immediate detection of leaks
- ▶ Wireless noise transmission
- ▶ Built-in LED light for night work
- ▶ Wireless range 20 m
- ▶ 10 level LED display

#### The HL 5 is this easy to use

- ▶ Switch on the device
- ▶ Place the HL 5 with the sensor on the object to be checked
- ▶ Turn on the wireless headphones
- ▶ Set the signal control to optimal audio transmission
- ▶ Watch the length of the LED display and listen to the sound
- ▶ If the display is stable, water is being drawn or there's a leak
- ▶ If the noise level dips briefly to zero, there is no leak
- ▶ Subsequently, measure at another location and narrow down the leak location

#### Technical data

Leak status	LED display
Level indicator	10 ary
Batteries - HL 5	2 x 1.5 V AA
- Headphones	2 x 1.5 V AAA
Filter	3 fixed filter settings (low, high, broadband)
Frequency range	40 ... 4000 Hz
Transmission range	up to 20 m
Light	LED light, integrated
Radio frequency	863 MHz
Dimensions (W x H x D)	35 x 114 x 25 mm
Battery life	approx. 50 h

#### Delivery includes

- ▶ HL 5 with FM transmitter using 863 MHz technology
- ▶ Wireless headphone with FM receiver
- ▶ 2 batteries 1.5 V AA for HL 5
- ▶ 2 batteries 1.5 V AAA for headphones
- ▶ 1 extension rod and magnet
- ▶ 1 transport case
- ▶ 1 set of operating instructions

#### Accessories

- ▶ Tripod (PAM U-D)
- ▶ Valve adapter (S42)
- ▶ Valve adapter (S20)